FORM 10

, Q.

Regulation 50 (5)

THE PUBLIC PROCUREMENT AND DISPOSAL OF PUBLIC ASSETS ACT, 2003 <u>RECORD OF MINUTES OF PRE-BID MEETING</u>

00045	2022-2023	SUPLS	UCDA
		Non-consultancy services	Entity
Sequence number	Financial year	Supplies/Works/	Code of Procuring and Disposing
	T.	Procurement Reference Number	

	Particulars of Procurement
Subject of procurement	SUPPLY AND INSTALLATION OF SOLAR DRIERS
Location of Pre-bid Meeting	COFFEE HSE 3 RD FLOOR ROOM 3.2
Date and time of Meeting	11:00AM: 20 TH STATEMSER 2002

The rack lay out shall fill the entire drier as per lay out described above and the number shall depend on the dimensions of the drier at a particular site.	What is the number of racks required on the solar drier?
The rack structure lay out shall be in rows running lengthwise within the tent with a middle walkway and access spacing of 1mt. The lower rack shall be fitted at 45 cms from the floor and the second at 1.2 mts. The width of each rack shall be 4 ft. (1.2 mt) The number of rows shall depend on the dimensions of the drier (which will vary depending on site).	What is the type, size and spacing of the racks in terms of length, width and height?
These are polypropylene strainer ropes which support the tent against the forces of wind. They should have a minimum of 3 strands and a diameter of 25 mm	What is the technical description of strip HPDPE ropes required?
The cyclone fans should be 3 and should be placed at a spacing of 3 equal intervals along the top of the tent	What is the number and spacing of cyclone fans required on the drier?
The structure will be made of galvanized pipes. The pillars will be made of 38mm pipes, the tops, 42 mm and the joiners,32mm (all internal diameters). The thickness of the pillars should be 2mm while the tops and joiners should be 1.5 – 2 mm. thickness.	What is the measurement of galvanized steel material in terms thickness?
The height shall be 2.5 mt measured as height for the verticle sides and 3.5mt. as the pitched height (height from floor to the highest point of tent).	

The successful bidder will have to use a parallel approach to drive the key elements of the project. Eg. fabricate and construct frame as importation of cover material is taking place. We shall monitor and take decision on time depending on how the project progresses. on-going	The delivery of 4months from contract signing appears to little considering importation of materials and time required for construction works of the foundation. Please review and provide for reasonable time to deliver the assignment.
Each solar drier shall have a lockable entrance door at one access end, made out of galvanized steel frame (32mm dia) with UV polythene sheet coverage of gauge 1000.Dimensions shall be 80*200 cm (W&H)	What is the type of entrance/exit door required on the solar drier?
The roof frame is the general one for the Greenhouse tent. The roof structure is "half-moon" and it should have a top purlin that holds the pillars at the top and lower purlins on each side that hold the gutter.	What is type of roof frames required (description)?
provide a strong cover that can last over 5 years- need for good handling and care practices, notwithstanding	
The thickness of 200 microns is equivalent to gauge 780 which in commercial terms is regarded as gauge 800. It is thick enough to	The 200 microns UV polythene sheets appears small given the size of the solar drier. What is the expected useful life of this drier.
Fastening shall be by use of either welding, bolts and nuts, or pipe joinery using threaded joints	What is the type of fastening required and acceptable?
The welding will be either galvanized welding, or mild steel welding with primer coating	What is the type welding on the steel frames required?

Page 3 of 5

Name:

Certification of minutes as a true record of the proceedings of the meeting:

Name:

Position: Chairperson of the meeting

Date: 20/9/2022

J

Signature:

Record of pre-bid meeting to be sent to all bidders who purchased or were issued with the bidding documents.

		04	S	80	9	No	
		Amust HETRE &	Edmund Byenbabari	Mahanga Stephen	HUMWESHENE NOBERD	Name and address	
		the & Gold Masery-	Graduate Taire Secretary	Polchaperoso	1500	Position	RECORD OF ATTENDANCE
		They smed went	UCPA PAU	CICA PDY	ucs A / Das	Company or department	J.E.
				(A)	white.	Signature	